

# Chrome plated brass hose union ball type bibtap, Blue lever.

## SIZES

Inlets Parallel, ISO 228-1 External Thread		
Range	1/2"	3/4"
Inlets Parallel, ISO 228-1 External Thread	262001	262002
ANSI-ASME B1.20.1 1983 Code - HU AT (14mm Spigot)	262004	-

## DIMENSIONS (mm)

Size	1/2"	3/4"
A	93	93
B	45	45
C	45	50
D	89	94
Weight kg*	0.26	0.32
Weight kg**	0.27	-

\* Code HU \*\* Code HU AT

## VALVE SUITABILITY

Steam	Water	Oil	Air	Gas Inert	Gas Combustible	Gas Corrosive	Gas Oxygen
✗	✓	✓	✗	✗	✗	✗	✗

## MATERIAL SPECIFICATION

Component	Material
Body	Brass, Chromium plated
Cap	Brass, Chromium plated
Ball	Brass, Chromium plated
Ball seal	PTFE
Spindle	Brass, Chromium plated
Spindle seal	NBR
Hose pipe	Brass, Chromium plated
Hose nut	Brass, Chromium plated
Hose union 'O' ring	NBR
Lever nut	Brass
Lever	A3 steel
Lever grip	PVC
Gland nut	Brass
Flow straightener	Polythene

## MAXIMUM PRESSURE TEMPERATURE RATINGS

Size	Maximum Working Pressure (bar)	
1/2 - 3/4"	(Cold working) Temperature up to 60°C	(Hot working) Temperature up to 100°C
	16.0	8

Temperature range 0°C +100°C (non shock)

