

Floatvalve Bronze seat BS 12114

Part one high pressure

FLOATVALVES to BS 12114

BS 12114 Part One. High Pressure. Bronze seat

| Pattern Number | Size | Piston Material | Backnut material | Seat Bore | Tail Length | Lever Length | Order Code |
|----------------|------|-----------------|------------------|-------------|-------------|--------------|------------|
| 12114 B-Y | ½" | B | B | No 3 (1/8") | 1¼" | 8¾" | BR 4097 |
| 12114 B-V | ½" | B | B | No 3 (1/8") | 17/8" | 10½" | BR 4127 |
| 12114 B | ¾" | B | B | No 6 (1/4") | 1¼" | 13" | BR 4078 |
| 12114 B | 1" | Bz | B | No 9 (3/8") | 1½" | 16" | BR 4079 |

BS 12114 Part One. Low Pressure. Bronze seat

| | | | | | | | |
|---------|----|---|---|-------------|-----|-----|---------|
| 12114 B | ½" | B | B | No 9 (3/8") | 1¼" | 8¾" | BR 5037 |
|---------|----|---|---|-------------|-----|-----|---------|

Note: Shading denotes variation to standard
 Specification key: B = Brass, N = Nylon, Bz = Bronze



FLOW RATE & SIZE SELECTION (gpm)

| | Static Pressure | | 12114 Floatvalve | | |
|-----------------|-----------------|--------|------------------|-------|-------|
| | psi | Feet | 1/8" | 1/4" | 3/8" |
| LOW PRESSURE | 0.5 | 1.15 | 0.20 | 0.82 | 1.84 |
| | 1.0 | 2.30 | 0.29 | 1.16 | 2.61 |
| | 2.0 | 4.60 | 0.41 | 1.65 | 3.69 |
| | 4.0 | 9.20 | 0.58 | 2.33 | 5.22 |
| | 7.0 | 16.10 | 0.77 | 3.08 | 6.90 |
| | 10.0 | 23.10 | 0.92 | 3.69 | 8.27 |
| | 15.0 | 34.60 | 1.13 | 4.52 | 10.10 |
| | 20.0 | 46.20 | 1.31 | 5.22 | 11.70 |
| | 25.0 | 57.70 | 1.46 | 5.82 | 13.00 |
| | 30.0 | 69.30 | 1.60 | 6.40 | 14.30 |
| MEDIUM PRESSURE | 35.0 | 80.80 | 1.73 | 6.90 | 15.50 |
| | 40.0 | 92.40 | 1.85 | 7.38 | 16.50 |
| | 50.0 | 115.00 | 2.06 | 8.24 | 18.50 |
| | 60.0 | 138.00 | 2.26 | 9.02 | 20.20 |
| | 70.0 | 161.00 | 2.44 | 9.74 | 21.80 |
| | 80.0 | 184.00 | 2.60 | 10.40 | 23.30 |
| | 90.0 | 207.00 | 2.76 | 11.00 | 24.70 |
| HIGH PRESSURE | 100.0 | 231.00 | 2.92 | 11.60 | 26.10 |
| | 110.0 | 254.00 | 3.06 | 12.20 | 27.40 |
| | 125.0 | 289.00 | 3.26 | 13.10 | 29.20 |
| | 150.0 | 346.00 | 3.58 | 14.30 | 32.00 |
| | 175.0 | 404.00 | 3.86 | 15.40 | 34.60 |
| 200.0 | 462.00 | 4.13 | 16.50 | 37.00 | |

Flow Rate and Size Selection Chart General Notes:

The discharge through a floatvalve is governed by the running pressure maintained at its inlet. In practice this is difficult to measure and so the tables shown indicate the 'estimated' flow rate in G.P.M that will occur at various static heads for each size of floatvalve or for each size of seat in floatvalves that accept a variety of seat sizes. The flow rates quoted will only occur when the floatvalve is fully open and will reduce as the water level in the tank rises. Excessive pipe runs to the floatvalve will result in lower running pressures and thus reduced flow rates.

Note: Where the same flow rate is quoted for 2 sizes of floatvalve, select the smaller size if the indicated flow rate is more than 5% in excess of the flow rate required.

MATERIAL SPECIFICATION

| Component | Material |
|------------------------------|-------------|
| Body | Brass |
| Body cap | Brass |
| Lever | Brass |
| Lever nut | Brass |
| Cotter pin | Brass |
| Body union nut | Brass |
| Tail pipe | Brass |
| Union nut washer | Fibre |
| Back nut washer / Spigot nut | Brass/Nylon |
| Seals | Bronze |
| Piston | Brass |
| Piston washer | NBR |
| Cap seal | NBR |