

Floats for BR float operated valves

PLASTIC FLOAT SIZES

Range	3"	4½"	5"	6"	8"	10"	12"
Code	BR 6022	BR 6032	BR 6033	BR 6025	BR 6028	BR 6029	BR 6038

DIMENSIONS

Range	3"	4½"	5"	6"	8"	10"	12"
Connection to lever arm*	5/16" W	5/16" W	5/16" W	3/8" W	3/8" W	1/2" W	1/2" W
Weight kg	0.03	0.092	0.114	0.168	0.408	0.803	0.914



COPPER FLOAT SIZES

Range	4½"	5½"	6"	8"	10"	12"	14"	15"	16"
Code	BR 6001	BR 6003	BR 6004	BR 6006	BR 6008	BR 6009	BR 6010	BR 6011	BR 6012
Weight kg	0.121	0.183	0.219	0.442	0.686	1.005	2.42	2.39	2.766



BRASS STUDS FOR COPPER FLOATS

Copper float requires							
Range (Float size)	4½"	5½"	6"	8"	10"	12"	
Code	BR 6039	BR 6040	BR 6041	BR 6042	BR 6043	BR 6044	
Size	5/16" W	3/8" W	7/16" W	9/16" W	9/16" W	5/8" W	
Weight kg	0.020	0.020	0.055	0.104	0.098	0.187	



CLAWS FOR COPPER FLOATS

Range	14"	15"	16"
Code	BR 6047	BR 6048	BR 6049
Size	9/16" W	3/4" W	7/8" W
Weight kg	0.3322	0.313	0.532



* W - Whitworth thread

Note: Studs generally required for float valves up to 2", Claws for 2 - 6" valves.

Note: Ball floats are only supplied in export shipments.