


# Chromium plated straight pattern brass service valve, copper x swivel union

SIZES	
Range	15mm x 1/2"
Code	BR 1007

DIMENSIONS (mm)	
Range	
A	57
Weight kg	0.11

MATERIAL SPECIFICATION	
Component	Material
Body	CP Brass
Ball	CP Brass
Ball circlip	Stainless steel
Stem	CP Brass
Stem 'O' ring	EPDM
Ball seals	PTFE
Compression nuts	CP Brass
Spigot	CP Brass
Swivel nut	CP Brass
Washer	Red fibre (non asbestos)

MINIMUM OPERATING PRESSURE RATINGS			
Size	Minimum Operating Pressure (bar)	Maximum Cold Working Pressure (bar)	Maximum Hot Working Pressure (bar)
15 to 22mm	No minimum operating pressure	Temperatures up to 30°C	Temperatures up to 120°C
	-	16.0	5.0



# 816 Brass spring safety valve, male thread (Export version\*)

SIZES		
Range	1/2"	3/4"
Code	538011	538012

DIMENSIONS (mm)		
Range		
A	47	51
Weight kg	-	-

MATERIAL SPECIFICATION	
Component	Material
Body	Brass
Cap	Brass
Setting lock nut	Brass
Spring	Stainless steel
Inlet seat	Brass

MINIMUM OPERATING PRESSURE RATINGS	
Size	Pressure Setting Range
1/2 to 3/4"	28 - 38 lb/in <sup>2</sup>

